




JUWEL TLM-Series Pneumatic Torque Wrench

- ° Torque range from 150 to 5,000 Nm
- Standard (XX4) or heavy loadversion (XX5) with modular gearbox design (see dimensional drawing)
- High degree of working ergonomics thanks to vibration-free and low-noise application behaviour
- Repeat accuracy of +/- 5% for the same bolting operation
- 2-speed right/left gearbox with a total of 44 torque steps
- ° Drive unit freely rotatable through 360°
- Support made of high-strength investment casting individual designs also possible on request thanks to in-house CNC manufacturing



Subject to technical changes and errors.

Technical Data



Special function: Two tools in one: Stepless locking of the control unit allows all variations between a straight and angled torque wrench.

Тур/Туре	TLM-84	TLM-104/105	TLM-244/245	TLM-354/355	TLM-505
Antriebsvierkant/Square drive A	3/4" / 1"	1"	1"	1 1/2"	1 1/2"
Artikelnummer Schwerlast/ Item number heavy load		58 105 310	58 245 320	58 355 330	58 505 340
Artikelnummer Standard/ Item number standard	50 084 300	58 104 310	58 244 320	58 354 330	-
Drehmoment/Torque (Nm)	40 - 880	40 - 1.200	70 - 2.500	70 - 4.000	100 - 5.000
Gewicht Abstützung/ Weight reaction arm (kg)	1.6	1.6	1.6	3.5	3.5
Gewicht Standard/ Weight Standard (kg)	9/9,5	9.5	9.5	10.5	-
Gewicht Schwerlast/ Weight heavy load (kg)	-	10.6	10.6	11.6	12.6
Höhe/Height C (mm)	55/75	75	75	95	95
Höhe/Height H (mm)	250/270	270	300	330	360
Leerlaufdrehzahl (U/min)/ Idle speed (r/min)	19	19	8.5	7.5	2
Ø Getriebe Schwerlast/ Gear heavy load D (mm)	-	99	99	99	99
Ø Getriebe Standard/ Gear standard D (mm)	88	88	88	88	-

More? Follow us!



in

► YouTube

Juwel-Schraubtechnik GmbH

@ernstbergersohnejuwel-schr8147